



PRODUCT DESCRIPTION

4350 Smooth Paper Pallet Protek™ is standard weight saturated paper coated with a medium tack rubber adhesive designed specifically as a premasking of screen print pallets. Its rubber-based adhesive resists solvents & high temperatures of flash curing.

Adhesive	Rubber-based
Color	White/Translucent
Caliper, facestock	100-113 microns (4.0 -4.5 mils)
Caliper, facestock + adhesive	125-138 microns (5.0 - 5.5 mils)
Adhesion to Stainless Steel	13 – 15 N/100mm (12 – 14 oz.)
Tensile	297 N/100mm (17lb./in)
Elongation	3-4%
Tear Resistance (grams)	50
Shelf life Stored at 22°C (72°F)/ 50-55 % RH	1 year

FEATURES & BENEFITS

- By pre-covering your pallets with 4350 Pallet Protek™ and spraying the paper tape instead of the pallet, press clean up is simply a matter of removing and discarding the tape. The whole process is fast and easy.
- To save time and increase shop productivity is to apply several layers of 4350 Pallet Protek™ tape to a pallet. When you need a clean sheet of pallet protection tape, just pull off the top layer. By marking the base layer with a large “X”, a printer will be alerted that he need reapply additional layers.
- Unwinds easily all the way to the core for trouble-free handling.

APPLICATIONS

- Pallet protection tape for textile printing.

Important Notice: All R Tape products are subject to continuous quality control throughout the manufacturing process and are warranted to be free from manufacturing defects. R Tape stands behind its products and will replace or credit any defective material. Because R Tape products are used for a variety of applications, the purchaser is responsible for determining the suitability and performance of this product for their specific purpose, prior to use and the purchaser shall assume all risks regarding such use.

R Tape Corporation

6 Ingersoll Road, South Plainfield, NJ 07080
908-753-5570 Fax 908-753-5014 800-440-1250
E-mail: sales@rtape.com
www.rtape.com

R Tape Europe

Industriezone Langevoorde
Groendeeff 35 9880 Aalter, Belgium
+32.9.216.6700 Fax: +32.9.216.6709
E-mail: sales@rtape.be